

tesa® PRO 66743



Mounting Wallpaper & Plaster

Product Information

tesa PRO Mounting Wallpaper & Plaster - Strong and lasting tape - Double-sided siliconised paper - For permanent applications - Ideal for indoor use

tesa PRO Mounting Wallpaper & Plaster

When clients want you to attach objects to textured surfaces without using nails or screws, use tesa PRO Mounting Wallpaper & Plaster. The double-sided tape is designed to hold onto sensitive surfaces. Its formula compensates minor surface irregularities and simplifies craftsmen's work. Be able to hang up artwork inside of buildings or hang up signs in garages. 1 m strip of tape can hold up to 10 kg.

Apply in vertical strips and along the full length of the object. Press down firmly on the mounting tape for at least five seconds on a dust-free surface.

Features

- *Don't use regular tape on wallpaper and plaster: This professional mounting tape is specifically designed to hold on textured surfaces
- *Permanent and reliable hold without damaging the wall: tesa PRO Mounting Wallpaper & Plaster makes use of screws, plugs or nails obsolete - for fast and easy mounting with no tools necessary
- *Ideal for interior use: Strong double-sided adhesive tape for secure fixing of flat objects such as signs and more
- *Easy to use: The mounting tape can be cut into individual small or large pieces for an adhesive strip in the optimized size
- *Scope of delivery: 1 x tesa PRO Mounting Wallpaper & Plaster tape -For permanent applications - Material: Synthetic rubber, Backing: PE-foam

Application

Easy to apply:

- In order for the mounting tape to develop its full holding power, the object and surface must be free of dust, dirt and grease.
- Don't touch the open adhesive surface as it could impair the adhesive strength.
- Affix vertical strips that correspond to the entire length of the object. Reinforce the upper portion with shorter strips.
- For removal, carefully pull the mounting tape parallel from the wall. As the mounting tapes are intended for permanent use, material residues may remain on the object. Try to remove with tesa adhesive remover.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

- | | | | |
|--------------------|---------|--------------------|----------------------|
| • Backing material | PE foam | • Type of adhesive | synthetic rubber |
| • Colour | white | • Colour of liner | white with tesa logo |
| • Total thickness | 1350 µm | | |

Distributor

+34 912 30 24 69

tesa® PRO 66743



Mounting Wallpaper & Plaster

Product Information

Adhesion to

• Steel (initial)	25.0 N/cm	• PET (covered side, initial)	25.0 N/cm
• Steel (covered side, initial)	20.0 N/cm	• PP (initial)	23.0 N/cm
• Aluminium (initial)	23.0 N/cm	• PP (covered side, initial)	17.0 N/cm
• Aluminium (covered side, initial)	18.0 N/cm	• PS (initial)	25.0 N/cm
• PC (initial)	22.0 N/cm	• PS (covered side, initial)	20.0 N/cm
• PC (covered side, initial)	21.0 N/cm	• PVC (initial)	25.0 N/cm
• PE (initial)	22.0 N/cm	• PVC (covered side, initial)	22.0 N/cm
• PE (covered side, initial)	16.0 N/cm	• ABS (after 14 days)	10.0 N/cm
• PET (initial)	25.0 N/cm		

Properties

• Temperature resistance short term	40 °C	• Ageing resistance (UV)	●●●
• Temperature resistance long term	40 °C	• Humidity resistance	●
• Tack	●●●	• Removability after 14 days (23°C)	●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Distributor

+34 912 30 24 69